



PARKES SHIRE COUNCIL

**BOGAN GATE
FLOOD RISK MANAGEMENT STUDY AND PLAN**

OCTOBER 2025

VOLUME 2 – FIGURES

COPYRIGHT NOTICE



This document, Bogan Gate Flood Risk Management Study and Plan, is licensed under the [Creative Commons Attribution 4.0 Licence](#), unless otherwise indicated.

Please give attribution to: © Parkes Shire Council 2025

We also request that you observe and retain any notices that may accompany this material as part of the attribution.

Notice Identifying Other Material and/or Rights in this Publication:

The author of this document has taken steps to both identify third-party material and secure permission for its reproduction and reuse. However, please note that where these third-party materials are not licensed under a Creative Commons licence, or similar terms of use, you should obtain permission from the rights holder to reuse their material beyond the ways you are permitted to use them under the [Copyright Act 1968](#). Please see the Table of References at the rear of this document for a list identifying other material and/or rights in this document.

Further Information

For further information about the copyright in this document, please contact:

Parkes Shire Council

2 Cecile Street, Parkes

council@parkes.nsw.gov.au

+61 2 6862 3946

DISCLAIMER


*The [Creative Commons Attribution 4.0 Licence](#) contains a Disclaimer of Warranties and Limitation of Liability. In addition: ***This document (and its associated data or other collateral materials, if any, collectively referred to herein as the 'document') were produced by Lyall & Associates Consulting Water Engineers for Parkes Shire Council only. The views expressed in the document are those of the author(s) alone, and do not necessarily represent the views of Parkes Shire Council. Reuse of this study or its associated data by anyone for any other purpose could result in error and/or loss. You should obtain professional advice before making decisions based upon the contents of this document.****

LIST OF FIGURES (MAIN REPORT)

- 1.1 Location Plan

- 2.1 Catchment Plan
- 2.2 Existing Stormwater Drainage System at Bogan Gate (2 Sheets)
- 2.3 Indicative Extent and Depths of Inundation – 1% AEP (3 Sheets)
- 2.4 Indicative Extent and Depths of Inundation – PMF (3 Sheets)
- 2.5 Longitudinal Section along Orange-Broken Hill Railway Line between Olive Grove Lane and Overland Road – Design Storm Events
- 2.6 Time of Rise of Floodwaters (2 Sheets)
- 2.7 Indicative Extent of Inundation and Location of Vulnerable Development and Critical Infrastructure (3 Sheets)
- 2.8 Sensitivity of Flood Behaviour to 20% Increase in Hydraulic Roughness Values – 1% AEP
- 2.9 Sensitivity of Flood Behaviour to Partial Blockage of Hydraulic Structures - 1% AEP
- 2.10 Sensitivity of Flood Behaviour to 10% Increase in Rainfall Intensity – 1% AEP
- 2.11 Sensitivity of Flood Behaviour to 30% Increase in Rainfall Intensity – 1% AEP
- 2.12 Impact of Increased Rainfall Intensities on Extent of Flooding – 1% AEP
- 2.13 Flood Hazard Vulnerability Classification – 1% AEP (3 Sheets)
- 2.14 Flood Hazard Vulnerability Classification – PMF (3 Sheets)
- 2.15 Hydraulic Categorisation of Floodplain – 1% AEP (3 Sheets)
- 2.16 Hydraulic Categorisation of Floodplain – PMF (3 Sheets)
- 2.17 Parkes LEP 2012 Zoning

- 3.1 Impact of Bogan Gate Potential Flood Modification Measure 1 (BG_PFMM1) on Flood Behaviour (2 Sheets)
- 3.2 Impact of Bogan Gate Potential Flood Modification Measure 3 (BG_PFMM3) on Flood Behaviour (3 Sheets)
- 3.3 Flooding Patterns in Vicinity of Existing Carlachy Railway Bridge under Pre- and Post-BG_PFMM3 Conditions – 5% AEP
- 3.4 Flooding Patterns in Vicinity of Existing Carlachy Railway Bridge under Pre- Post-BG_PFMM3 Conditions – 2% AEP
- 3.5 Flooding Patterns in Vicinity of Existing Carlachy Railway Bridge under Pre-Post-BG_PFMM3 Conditions – 1% AEP
- 3.6 Impact of Bogan Gate Potential Flood Modification Measure 4 (BG_PFMM4) on Flood Behaviour (3 Sheets)
- 3.7 Flood Emergency Response Planning Classifications – 5% AEP
- 3.8 Flood Emergency Response Planning Classifications – 1% AEP
- 3.9 Flood Emergency Response Planning Classifications – PMF



N
4 0 4 8 12 km
Scale: 1:400,000

Lyall &
Associates


LEGEND

- ★ BoM All Weather Station (AWS)
- ★ BoM Daily Rainfall Station
- ★ BoM Flood Warning Network (FWN) Rain Gauge
- ★ Privately Owned Rain Gauge
- Study Catchment
- LGA Boundary
- River Basin Catchment Boundary

BOGAN GATE FLOOD RISK MANGEMENT STUDY AND PLAN

Figure 1.1

LOCATION PLAN



LEGEND

- LGA Boundary
- Catchment Boundary
- ★ BoM All Weather Station (AWS)
- ★ BoM Daily Rainfall Station
- ★ BoM Flood Warning Network (FWN) Rain Gauge
- ★ Privately Owned Rain Gauge

BOGAN GATE

FLOOD RISK MANGEMENT STUDY AND PLAN


Figure 2.1

CATCHMENT PLAN

Scale: 1:200,000

2 0 2 4 6 km

Lyall & Associates





N
200 0 200 400 600 m
Scale: 1:20,000

Lyall & Associates


LEGEND


- | | |
|---|--|
| — LGA Boundary | Village Centre |
| — Rural Levee/Embankment | ● Homestead |
| ● Existing Stormwater Drainage System | x Causeway |
| Natural Surface Elevation Contour (1m Interval) | x Bridge/Major Culvert |

BOGAN GATE FLOOD RISK MANGEMENT STUDY AND PLAN

Figure 2.2
(Sheet 2 of 2)

EXISTING STORMWATER DRAINAGE SYSTEM AT BOGAN GATE





Indicative Depth of Inundation (m)

Blue	0.10 to 0.20
Dark Blue	0.20 to 0.30
Green	0.30 to 0.40
Light Green	0.40 to 0.50
Yellow	0.50 to 0.60
Orange	0.60 to 0.70
Dark Orange	0.70 to 0.80
Red-Orange	0.80 to 0.90
Red	0.90 to 1.00
Dark Red	> 1.00

NOTE:
Depth legend differs from that shown on Figures 4.3 to 4.4 and Figures 6.1 to 6.7.

Scale: 1:40,000

0 400 800 1,200 m

NOTE:
The ground surface model incorporated in TUFLOW is based on LiDAR survey which has been sampled on a 3 m (min) grid and does not necessarily incorporate localised features which can influence flooding behaviour in individual allotments.

Flood depths are therefore approximate only and require interpretation by a suitably qualified engineer to determine flooding behaviour in individual allotments. Any assessment of flooding in individual allotments may also require a site survey.

The allotment boundaries shown are based on the NSW State Database obtained from the Six Maps online database and may not represent the true property boundaries in the study area.

LEGEND


- LGA Boundary
- Two-Dimensional Model Boundary
- Modelled Stormwater Drainage System
- Village Centre
- Homesteads

BOGAN GATE

FLOOD RISK MANGEMENT STUDY AND PLAN

Figure 2.3
(Sheet 2 of 3)

INDICATIVE EXTENT AND DEPTHS OF INUNDATION
1% AEP



Indicative Depth of Inundation (m)

Blue	0.10 to 0.20
Dark Blue	0.20 to 0.30
Green	0.30 to 0.40
Light Green	0.40 to 0.50
Yellow	0.50 to 0.60
Orange	0.60 to 0.70
Dark Orange	0.70 to 0.80
Red-Orange	0.80 to 0.90
Red	0.90 to 1.00
Dark Red	> 1.00

NOTE:
Depth legend differs from that shown on Figures 4.3 to 4.4 and Figures 6.1 to 6.7.

Scale: 1:10,000

100 0 100 200 300 m

NOTE:
The ground surface model incorporated in TUFLOW is based on LiDAR survey which has been sampled on a 3 m (min) grid and does not necessarily incorporate localised features which can influence flooding behaviour in individual allotments.

Flood depths are therefore approximate only and require interpretation by a suitably qualified engineer to determine flooding behaviour in individual allotments. Any assessment of flooding in individual allotments may also require a site survey.

The allotment boundaries shown are based on the NSW State Database obtained from the Six Maps online database and may not represent the true property boundaries in the study area

LEGEND


- LGA Boundary
- Two-Dimensional Model Boundary
- Modelled Stormwater Drainage System
- Village Centre
- Homesteads

BOGAN GATE

FLOOD RISK MANGEMENT STUDY AND PLAN

Figure 2.3
(Sheet 3 of 3)

INDICATIVE EXTENT AND DEPTHS OF INUNDATION
1% AEP



Indicative Depth of Inundation (m)

0.10 to 0.20
0.20 to 0.40
0.40 to 0.60
0.60 to 0.80
0.80 to 1.00
1.00 to 1.20
1.20 to 1.40
1.40 to 1.60
1.60 to 1.80
1.80 to 2.00
> 2.00

Scale: 1:100,000

1 0 1 2 3 km

NOTE:

The ground surface model incorporated in TUFLOW is based on LiDAR survey which has been sampled on a 3 m (min) grid and does not necessarily incorporate localised features which can influence flooding behaviour in individual allotments.

Flood depths are therefore approximate only and require interpretation by a suitably qualified engineer to determine flooding behaviour in individual allotments. Any assessment of flooding in individual allotments may also require a site survey.

The allotment boundaries shown are based on the NSW State Database obtained from the Six Maps online database and may not represent the true property boundaries in the study area


LEGEND


- LGA Boundary
- Two-Dimensional Model Boundary
- Modelled Stormwater Drainage System
- Village Centre
- Homesteads

BOGAN GATE FLOOD RISK MANAGEMENT STUDY AND PLAN

Figure 2.4 (Sheet 1 of 3)

INDICATIVE EXTENT AND DEPTHS OF INUNDATION PMF





Indicative Depth of Inundation (m)

0.10 to 0.20
0.20 to 0.40
0.40 to 0.60
0.60 to 0.80
0.80 to 1.00
1.00 to 1.20
1.20 to 1.40
1.40 to 1.60
1.60 to 1.80
1.80 to 2.00
> 2.00

Scale: 1:10,000

Lyall & Associates

NOTE:
The ground surface model incorporated in TUFLOW is based on LiDAR survey which has been sampled on a 3 m (min) grid and does not necessarily incorporate localised features which can influence flooding behaviour in individual allotments.

Flood depths are therefore approximate only and require interpretation by a suitably qualified engineer to determine flooding behaviour in individual allotments. Any assessment of flooding in individual allotments may also require a site survey.


The allotment boundaries shown are based on the NSW State Database obtained from the Six Maps online database and may not represent the true property boundaries in the study area









- LEGEND**
- LGA Boundary
 - Two-Dimensional Model Boundary
 - Modelled Stormwater Drainage System
 - Village Centre
 - Homesteads

○ Road/Rail Design Flood Data Location and Identifier

**BOGAN GATE
FLOOD RISK MANGEMENT STUDY AND PLAN**






Figure 2.4
(Sheet 3 of 3)
**INDICATIVE EXTENT AND DEPTHS OF INUNDATION
PMF**





NOTES:
Refer Figures 2.3 to 2.4 for Peak Flood Level Locations.

- LEGEND**
- Road/Rail Level
 - 0.2% AEP
 - 0.5% AEP
 - 1% AEP
 - 2% AEP
 - 5% AEP
 - 10% AEP
 - 20% AEP




LEGEND


— — — — —	Road/Rail Level	—	2% AEP
—	0.2% AEP	—	5% AEP
—	0.5% AEP	—	10% AEP
—	1% AEP	—	20% AEP




NOTES:
Refer **Figures 2.3** and **2.4** for Peak Flood Level Locations.














Scale: 1:100,000

1 0 1 2 3 km

Lyall & Associates

NOTE:

The ground surface model incorporated in TUFLOW is based on LiDAR survey which has been sampled on a 3 m (min) grid and does not necessarily incorporate localised features which can influence flooding behaviour in individual allotments.

Flood depths are therefore approximate only and require interpretation by a suitably qualified engineer to determine flooding behaviour in individual allotments. Any assessment of flooding in individual allotments may also require a site survey.

The allotment boundaries shown are based on the NSW State Database obtained from the Six Maps online database and may not represent the true property boundaries in the study area

LEGEND

- LGA Boundary
- Two-Dimensional Model Boundary
- Modelled Stormwater Drainage System
- Village Centre
- Homesteads


BOGAN GATE


FLOOD RISK MANGEMENT STUDY AND PLAN

Figure 2.10

SENSITIVITY OF FLOOD BEHAVIOUR TO 10% INCREASE IN RAINFALL INTENSITY

1% AEP





Scale: 1:100,000

1 0 1 2 3 km

Lyall & Associates

NOTE:
The ground surface model incorporated in TUFLOW is based on LiDAR survey which has been sampled on a 3 m (min) grid and does not necessarily incorporate localised features which can influence flooding behaviour in individual allotments.

Flood depths are therefore approximate only and require interpretation by a suitably qualified engineer to determine flooding behaviour in individual allotments. Any assessment of flooding in individual allotments may also require a site survey.

The allotment boundaries shown are based on the NSW State Database obtained from the Six Maps online database and may not represent the true property boundaries in the study area

LEGEND

- LGA Boundary
- Two-Dimensional Model Boundary
- Modelled Stormwater Drainage System
- Village Centre
- Homesteads

1% AEP

1% AEP Rainfall Increased by 10%

1% AEP Rainfall Increased by 30%


BOGAN GATE


FLOOD RISK MANGEMENT STUDY AND PLAN

Figure 2.12

IMPACT OF INCREASED RAINFALL INTENSITIES ON EXTENT OF FLOODING

1% AEP





FLOOD HAZARD VULNERABILITY CLASSIFICATION

H1	Generally safe for vehicles, people and buildings.
H2	Unsafe for small vehicles.
H3	Unsafe for vehicles, children and the elderly.
H4	Unsafe for vehicles and people.
H5	Unsafe for vehicles and people. All building types vulnerable to structural damage. Some less robust building types vulnerable to failure.
H6	Unsafe for vehicles and people. All building types considered vulnerable to failure.

NOTE:

The ground surface model incorporated in TUFLOW is based on LiDAR survey which has been sampled on a 3 m (min) grid and does not necessarily incorporate localised features which can influence flooding behaviour in individual allotments.

Flood depths are therefore approximate only and require interpretation by a suitably qualified engineer to determine flooding behaviour in individual allotments. Any assessment of flooding in individual allotments may also require a site survey.

The allotment boundaries shown are based on the NSW State Database obtained from the Six Maps online database and may not represent the true property boundaries in the study area.

LEGEND

- LGA Boundary
- Two-Dimensional Model Boundary
- Modelled Stormwater Drainage System
- Village Centre
- Homesteads

BOGAN GATE

FLOOD RISK MANGEMENT STUDY AND PLAN


Figure 2.13
(Sheet 2 of 3)

FLOOD HAZARD VULNERABILITY CLASSIFICATION
1% AEP

Scale: 1:40,000


400 0 400 800 1,200 m

Lyall & Associates



FLOOD HAZARD VULNERABILITY CLASSIFICATION

- H1** Generally safe for vehicles, people and buildings.
- H2** Unsafe for small vehicles.
- H3** Unsafe for vehicles, children and the elderly.
- H4** Unsafe for vehicles and people.
- H5** Unsafe for vehicles and people. All building types vulnerable to structural damage. Some less robust building types vulnerable to failure.
- H6** Unsafe for vehicles and people. All building types considered vulnerable to failure.



Lyall & Associates

NOTE:
The ground surface model incorporated in TUFLOW is based on LiDAR survey which has been sampled on a 3 m (min) grid and does not necessarily incorporate localised features which can influence flooding behaviour in individual allotments.

Flood depths are therefore approximate only and require interpretation by a suitably qualified engineer to determine flooding behaviour in individual allotments. Any assessment of flooding in individual allotments may also require a site survey.

The allotment boundaries shown are based on the NSW State Database obtained from the Six Maps online database and may not represent the true property boundaries in the study area


LEGEND

- LGA Boundary
- - - Two-Dimensional Model Boundary
- Modelled Stormwater Drainage System
- Village Centre
- Homesteads

BOGAN GATE
FLOOD RISK MANGEMENT STUDY AND PLAN

Figure 2.13
(Sheet 3 of 3)

FLOOD HAZARD VULNERABILITY CLASSIFICATION
1% AEP



FLOOD HAZARD VULNERABILITY CLASSIFICATION

- H1 Generally safe for vehicles, people and buildings.
- H2 Unsafe for small vehicles.
- H3 Unsafe for vehicles, children and the elderly.
- H4 Unsafe for vehicles and people.
- H5 Unsafe for vehicles and people. All building types vulnerable to structural damage. Some less robust building types vulnerable to failure.
- H6 Unsafe for vehicles and people. All building types considered vulnerable to failure.

NOTE:

The ground surface model incorporated in TUFLOW is based on LiDAR survey which has been sampled on a 3 m (min) grid and does not necessarily incorporate localised features which can influence flooding behaviour in individual allotments.

Flood depths are therefore approximate only and require interpretation by a suitably qualified engineer to determine flooding behaviour in individual allotments. Any assessment of flooding in individual allotments may also require a site survey.

The allotment boundaries shown are based on the NSW State Database obtained from the Six Maps online database and may not represent the true property boundaries in the study area

LEGEND

- LGA Boundary
- Two-Dimensional Model Boundary
- Modelled Stormwater Drainage System
- Village Centre
- Homesteads

BOGAN GATE

FLOOD RISK MANGEMENT STUDY AND PLAN


Figure 2.14
(Sheet 1 of 3)

FLOOD HAZARD VULNERABILITY CLASSIFICATION
PMF

Scale: 1:100,000


1 0 1 2 3 km

Lyall & Associates



FLOOD HAZARD VULNERABILITY CLASSIFICATION

H1	Generally safe for vehicles, people and buildings.
H2	Unsafe for small vehicles.
H3	Unsafe for vehicles, children and the elderly.
H4	Unsafe for vehicles and people.
H5	Unsafe for vehicles and people. All building types vulnerable to structural damage. Some less robust building types vulnerable to failure.
H6	Unsafe for vehicles and people. All building types considered vulnerable to failure.



Lyall & Associates


NOTE:
The ground surface model incorporated in TUFLOW is based on LiDAR survey which has been sampled on a 3 m (min) grid and does not necessarily incorporate localised features which can influence flooding behaviour in individual allotments.

Flood depths are therefore approximate only and require interpretation by a suitably qualified engineer to determine flooding behaviour in individual allotments. Any assessment of flooding in individual allotments may also require a site survey.


The allotment boundaries shown are based on the NSW State Database obtained from the Six Maps online database and may not represent the true property boundaries in the study area.

LEGEND

	LGA Boundary
	Two-Dimensional Model Boundary
	Modelled Stormwater Drainage System
	Village Centre
	Homesteads



<



Scale: 1:100,000

1 0 1 2 3 km

Lyall & Associates

NOTE:

The ground surface model incorporated in TUFLOW is based on LiDAR survey which has been sampled on a 3 m (min) grid and does not necessarily incorporate localised features which can influence flooding behaviour in individual allotments.

Flood depths are therefore approximate only and require interpretation by a suitably qualified engineer to determine flooding behaviour in individual allotments. Any assessment of flooding in individual allotments may also require a site survey.

The allotment boundaries shown are based on the NSW State Database obtained from the Six Maps online database and may not represent the true property boundaries in the study area


LEGEND

- LGA Boundary
- Two-Dimensional Model Boundary
- Modelled Stormwater Drainage System
- Village Centre
- Homesteads
- Floodway
- Flood Storage
- Flood Fringe

BOGAN GATE FLOOD RISK MANAGEMENT STUDY AND PLAN

Figure 2.15
(Sheet 1 of 3)

HYDRAULIC CATEGORISATION OF FLOODPLAIN
1% AEP



Lyall & Associates

NOTE:
The ground surface model incorporated in TUFLOW is based on LiDAR survey which has been sampled on a 3 m (min) grid and does not necessarily incorporate localised features which can influence flooding behaviour in individual allotments.

Flood depths are therefore approximate only and require interpretation by a suitably qualified engineer to determine flooding behaviour in individual allotments. Any assessment of flooding in individual allotments may also require a site survey.

The allotment boundaries shown are based on the NSW State Database obtained from the Six Maps online database and may not represent the true property boundaries in the study area


LEGEND

- LGA Boundary
- Two-Dimensional Model Boundary
- Modelled Stormwater Drainage System
- Village Centre
- Homesteads
- Floodway
- Flood Storage
- Flood Fringe

BOGAN GATE
FLOOD RISK MANAGEMENT STUDY AND PLAN

Figure 2.15
(Sheet 2 of 3)

HYDRAULIC CATEGORISATION OF FLOODPLAIN
1% AEP



N
100 0 100 200 300 m
Scale: 1:10,000

Lyall & Associates

NOTE:
The ground surface model incorporated in TUFLOW is based on LiDAR survey which has been sampled on a 3 m (min) grid and does not necessarily incorporate localised features which can influence flooding behaviour in individual allotments.

Flood depths are therefore approximate only and require interpretation by a suitably qualified engineer to determine flooding behaviour in individual allotments. Any assessment of flooding in individual allotments may also require a site survey.

The allotment boundaries shown are based on the NSW State Database obtained from the Six Maps online database and may not represent the true property boundaries in the study area

LEGEND


- LGA Boundary
- Two-Dimensional Model Boundary
- Modelled Stormwater Drainage System
- Village Centre
- Homesteads

- Floodway
- Flood Storage
- Flood Fringe

BOGAN GATE FLOOD RISK MANAGEMENT STUDY AND PLAN

Figure 2.15
(Sheet 3 of 3)

HYDRAULIC CATEGORISATION OF FLOODPLAIN
1% AEP





1 0 1 2 3 km
Scale: 1:100,000

NOTE:
The ground surface model incorporated in TUFLOW is based on LiDAR survey which has been sampled on a 3 m (min) grid and does not necessarily incorporate localised features which can influence flooding behaviour in individual allotments.

Flood depths are therefore approximate only and require interpretation by a suitably qualified engineer to determine flooding behaviour in individual allotments. Any assessment of flooding in individual allotments may also require a site survey.

The allotment boundaries shown are based on the NSW State Database obtained from the Six Maps online database and may not represent the true property boundaries in the study area

LEGEND


- LGA Boundary
- Two-Dimensional Model Boundary
- Modelled Stormwater Drainage System
- Village Centre
- Homesteads

- Floodway
- Flood Storage
- Flood Fringe

BOGAN GATE
FLOOD RISK MANAGEMENT STUDY AND PLAN

Figure 2.16
(Sheet 1 of 3)

HYDRAULIC CATEGORISATION OF FLOODPLAIN
PMF



N

400

0

400

800

1,200 m

Scale: 1:40,000

NOTE:

The ground surface model incorporated in TUFLOW is based on LiDAR survey which has been sampled on a 3 m (min) grid and does not necessarily incorporate localised features which can influence flooding behaviour in individual allotments.

Flood depths are therefore approximate only and require interpretation by a suitably qualified engineer to determine flooding behaviour in individual allotments. Any assessment of flooding in individual allotments may also require a site survey.

The allotment boundaries shown are based on the NSW State Database obtained from the Six Maps online database and may not represent the true property boundaries in the study area

LEGEND

LGA Boundary

Two-Dimensional Model Boundary

Modelled Stormwater Drainage System

Village Centre

Homesteads

Floodway

Flood Storage

Flood Fringe



BOGAN GATE

FLOOD RISK MANAGEMENT STUDY AND PLAN

Figure 2.16
(Sheet 2 of 3)

HYDRAULIC CATEGORISATION OF FLOODPLAIN
PMF

Lyll & Associates



Lyall & Associates

NOTE:
The ground surface model incorporated in TUFLOW is based on LiDAR survey which has been sampled on a 3 m (min) grid and does not necessarily incorporate localised features which can influence flooding behaviour in individual allotments.

Flood depths are therefore approximate only and require interpretation by a suitably qualified engineer to determine flooding behaviour in individual allotments. Any assessment of flooding in individual allotments may also require a site survey.

The allotment boundaries shown are based on the NSW State Database obtained from the Six Maps online database and may not represent the true property boundaries in the study area

LEGEND


- LGA Boundary
- Two-Dimensional Model Boundary
- Modelled Stormwater Drainage System
- Village Centre
- Homesteads


- Floodway
- Flood Storage
- Flood Fringe


**BOGAN GATE
FLOOD RISK MANAGEMENT STUDY AND PLAN**

Figure 2.16
(Sheet 3 of 3)

HYDRAULIC CATEGORISATION OF FLOODPLAIN
PMF








50 0 50 100 150 m
Scale: 1:5000


Lyall & Associates


NOTE:
The ground surface model incorporated in TUFLOW is based on LiDAR survey which has been sampled on a 3 m (min) grid and does not necessarily incorporate localised features which can influence flooding behaviour in individual allotments.
Flood depths are therefore approximate only and require interpretation by a suitably qualified engineer to determine flooding behaviour in individual allotments. Any assessment of flooding in individual allotments may also require a site survey.
The allotment boundaries shown are based on the NSW State Database obtained from the Six Maps online database and may not represent the true property boundaries in the study area


IMPACT OF BOGAN GATE POTENTIAL FLOOD MODIFICATION MEASURE 1 (BG_PFMM1) ON FLOOD BEHAVIOUR


Figure 3.1
(Sheet 2 of 2)






















**BOGAN GATE
FLOOD RISK MANGEMENT STUDY AND PLAN**

Figure 3.6
(Sheet 2 of 3)

IMPACT OF BOGAN GATE POTENTIAL FLOOD MODIFICATION MEASURE 4 (BG_PFMM4)
ON FLOOD BEHAVIOUR





POTENTIAL EVACUATION ROUTES

- Potential Vehicular Evacuation Route
- Location where Potential Vehicular Evacuation Route is Subject to H2-H6 Hazardous Flooding

FLOOD EMERGENCY RESPONSE CLASSIFICATIONS

- Extent of Inundation
- Low Flood Island
- High Flood Island
- Rising Road Access
- Extent of Flood Emergency Response Classification

NOTE:
The ground surface model incorporated in TUFLOW is based on LiDAR survey which has been sampled on a 3 m (min) grid and does not necessarily incorporate localised features which can influence flooding behaviour in individual allotments.

Flood depths are therefore approximate only and require interpretation by a suitably qualified engineer to determine flooding behaviour in individual allotments. Any assessment of flooding in individual allotments may also require a site survey.

The allotment boundaries shown are based on the NSW State Database obtained from the Six Maps online database and may not represent the true property boundaries in the study area


LEGEND

- Modelled Stormwater Drainage System
- Village Centre
- Homesteads

BOGAN GATE
FLOOD RISK MANAGEMENT STUDY AND PLAN

Figure 3.7

FLOOD EMERGENCY RESPONSE PLANNING CLASSIFICATIONS
5% AEP



POTENTIAL EVACUATION ROUTES

- Potential Vehicular Evacuation Route
- Location where Potential Vehicular Evacuation Route is Subject to H2-H6 Hazardous Flooding

FLOOD EMERGENCY RESPONSE CLASSIFICATIONS

- Extent of Inundation
- Low Flood Island
- High Flood Island
- Rising Road Access
- Extent of Flood Emergency Response Classification

LEGEND

- Modelled Stormwater Drainage System
- Village Centre
- Homesteads

NOTE:
The ground surface model incorporated in TUFLOW is based on LiDAR survey which has been sampled on a 3 m (min) grid and does not necessarily incorporate localised features which can influence flooding behaviour in individual allotments.


Flood depths are therefore approximate only and require interpretation by a suitably qualified engineer to determine flooding behaviour in individual allotments. Any assessment of flooding in individual allotments may also require a site survey.

The allotment boundaries shown are based on the NSW State Database obtained from the Six Maps online database and may not represent the true property boundaries in the study area

BOGAN GATE
FLOOD RISK MANAGEMENT STUDY AND PLAN

Figure 3.8

FLOOD EMERGENCY RESPONSE PLANNING CLASSIFICATIONS
1% AEP



POTENTIAL EVACUATION ROUTES

- Potential Vehicular Evacuation Route
- Location where Potential Vehicular Evacuation Route is Subject to H2-H6 Hazardous Flooding

FLOOD EMERGENCY RESPONSE CLASSIFICATIONS

- Extent of Inundation
- Low Flood Island
- High Flood Island
- Rising Road Access
- Extent of Flood Emergency Response Classification

Scale: 1:10,000

NOTE:
The ground surface model incorporated in TUFLOW is based on LiDAR survey which has been sampled on a 3 m (min) grid and does not necessarily incorporate localised features which can influence flooding behaviour in individual allotments.

Flood depths are therefore approximate only and require interpretation by a suitably qualified engineer to determine flooding behaviour in individual allotments. Any assessment of flooding in individual allotments may also require a site survey.

The allotment boundaries shown are based on the NSW State Database obtained from the Six Maps online database and may not represent the true property boundaries in the study area

LEGEND

- Modelled Stormwater Drainage System
- Village Centre
- Homesteads

BOGAN GATE
FLOOD RISK MANAGEMENT STUDY AND PLAN

Figure 3.9


FLOOD EMERGENCY RESPONSE PLANNING CLASSIFICATIONS
PMF

APPENDIX B

ADDITIONAL FIGURES SHOWING DESIGN FLOOD BEHAVIOUR AT BOGAN GATE

LIST OF FIGURES (APPENDIX B)

- B1.1 Indicative Extent and Depths of Inundation – 20% AEP (3 Sheets)
- B1.2 Indicative Extent and Depths of Inundation – 10% AEP (3 Sheets)
- B1.3 Indicative Extent and Depths of Inundation – 5% AEP (3 Sheets)
- B1.4 Indicative Extent and Depths of Inundation – 2% AEP (3 Sheets)
- B1.5 Indicative Extent and Depths of Inundation – 0.5% AEP (3 Sheets)
- B1.6 Indicative Extent and Depths of Inundation – 0.2% AEP (3 Sheets)



1 0 1 2 3 km
Scale: 1:100,000

Lyll & Associates

NOTE:
The ground surface model incorporated in TUFLOW is based on LiDAR survey which has been sampled on a 3 m (min) grid and does not necessarily incorporate localised features which can influence flooding behaviour in individual allotments.

Flood depths are therefore approximate only and require interpretation by a suitably qualified engineer to determine flooding behaviour in individual allotments. Any assessment of flooding in individual allotments may also require a site survey.

The allotment boundaries shown are based on the NSW State Database obtained from the Six Maps online database and may not represent the true property boundaries in the study area


LEGEND

- LGA Boundary
- - - Two-Dimensional Model Boundary
- Modelled Stormwater Drainage System
- Village Centre
- Homesteads

**BOGAN GATE
FLOOD RISK MANGEMENT STUDY AND PLAN**

Figure B1.1
(Sheet 1 of 3)

INDICATIVE EXTENT AND DEPTHS OF INUNDATION
20% AEP



Indicative Depth of Inundation (m)

0.10 to 0.20
0.20 to 0.30
0.30 to 0.40
0.40 to 0.50
0.50 to 0.60
0.60 to 0.70
0.70 to 0.80
0.80 to 0.90
0.90 to 1.00
> 1.00

NOTE:
The ground surface model incorporated in TUFLOW is based on LiDAR survey which has been sampled on a 3 m (min) grid and does not necessarily incorporate localised features which can influence flooding behaviour in individual allotments.

Flood depths are therefore approximate only and require interpretation by a suitably qualified engineer to determine flooding behaviour in individual allotments. Any assessment of flooding in individual allotments may also require a site survey.

The allotment boundaries shown are based on the NSW State Database obtained from the Six Maps online database and may not represent the true property boundaries in the study area.

LEGEND

- LGA Boundary
- Two-Dimensional Model Boundary
- Modelled Stormwater Drainage System
- Village Centre
- Homesteads

BOGAN GATE
FLOOD RISK MANGEMENT STUDY AND PLAN


Figure B1.1
(Sheet 2 of 3)

INDICATIVE EXTENT AND DEPTHS OF INUNDATION
20% AEP

Scale: 1:40,000

400 0 400 800 1,200 m

Lyall & Associates






Indicative Depth of Inundation (m)



REFER SHEET 2



NOTE:
The ground surface model incorporated in TUFLOW is based on LiDAR survey which has been sampled on a 3 m (min) grid and does not necessarily incorporate localised features which can influence flooding behaviour in individual allotments.

Flood depths are therefore approximate only and require interpretation by a suitably qualified engineer to determine flooding behaviour in individual allotments. Any assessment of flooding in individual allotments may also require a site survey.

The allotment boundaries shown are based on the NSW State Database obtained from the Six Maps online database and may not represent the true property boundaries in the study area

LEGEND


- LGA Boundary
- - - Two-Dimensional Model Boundary
- Modelled Stormwater Drainage System
- Village Centre
- Homesteads

BOGAN GATE
FLOOD RISK MANGEMENT STUDY AND PLAN


Figure B1.2
(Sheet 1 of 3)

INDICATIVE EXTENT AND DEPTHS OF INUNDATION
10% AEP

Lyall & Associates



Indicative Depth of Inundation (m)




Lyall & Associates

NOTE:
The ground surface model incorporated in TUFLOW is based on LiDAR survey which has been sampled on a 3 m (min) grid and does not necessarily incorporate localised features which can influence flooding behaviour in individual allotments.
Flood depths are therefore approximate only and require interpretation by a suitably qualified engineer to determine flooding behaviour in individual allotments. Any assessment of flooding in individual allotments may also require a site survey.
The allotment boundaries shown are based on the NSW State Database obtained from the Six Maps online database and may not represent the true property boundaries in the study area.

- LEGEND**
- LGA Boundary
 - Two-Dimensional Model Boundary
 - Modelled Stormwater Drainage System
 - Village Centre
 - Homesteads

BOGAN GATE
FLOOD RISK MANGEMENT STUDY AND PLAN
Figure B1.2
(Sheet 2 of 3)
INDICATIVE EXTENT AND DEPTHS OF INUNDATION
10% AEP



Indicative Depth of Inundation (m)

- 0.10 to 0.20
- 0.20 to 0.30
- 0.30 to 0.40
- 0.40 to 0.50
- 0.50 to 0.60
- 0.60 to 0.70
- 0.70 to 0.80
- 0.80 to 0.90
- 0.90 to 1.00
- > 1.00



100 0 100 200 300 m
Scale: 1:10,000

Lyll & Associates

NOTE:

The ground surface model incorporated in TUFLOW is based on LiDAR survey which has been sampled on a 3 m (min) grid and does not necessarily incorporate localised features which can influence flooding behaviour in individual allotments.

Flood depths are therefore approximate only and require interpretation by a suitably qualified engineer to determine flooding behaviour in individual allotments. Any assessment of flooding in individual allotments may also require a site survey.

The allotment boundaries shown are based on the NSW State Database obtained from the Six Maps online database and may not represent the true property boundaries in the study area

LEGEND

- LGA Boundary
- Two-Dimensional Model Boundary
- Modelled Stormwater Drainage System
- Village Centre
- Homesteads

**BOGAN GATE
FLOOD RISK MANGEMENT STUDY AND PLAN**


Figure B1.2
(Sheet 3 of 3)

INDICATIVE EXTENT AND DEPTHS OF INUNDATION
10% AEP




Scale: 1:100,000

Lyall & Associates



Indicative Depth of Inundation (m)




Lyal & Associates

NOTE:
The ground surface model incorporated in TUFLOW is based on LiDAR survey which has been sampled on a 3 m (min) grid and does not necessarily incorporate localised features which can influence flooding behaviour in individual allotments.
Flood depths are therefore approximate only and require interpretation by a suitably qualified engineer to determine flooding behaviour in individual allotments. Any assessment of flooding in individual allotments may also require a site survey.
The allotment boundaries shown are based on the NSW State Database obtained from the Six Maps online database and may not represent the true property boundaries in the study area.

- LEGEND**
- LGA Boundary
 - - - Two-Dimensional Model Boundary
 - Modelled Stormwater Drainage System
 - Village Centre
 - Homesteads

BOGAN GATE
FLOOD RISK MANGEMENT STUDY AND PLAN
Figure B1.3
(Sheet 2 of 3)
INDICATIVE EXTENT AND DEPTHS OF INUNDATION
5% AEP



Indicative Depth of Inundation (m)

- 0.10 to 0.20
- 0.20 to 0.30
- 0.30 to 0.40
- 0.40 to 0.50
- 0.50 to 0.60
- 0.60 to 0.70
- 0.70 to 0.80
- 0.80 to 0.90
- 0.90 to 1.00
- > 1.00



100 0 100 200 300 m
Scale: 1:10,000

Lyll & Associates

NOTE:
The ground surface model incorporated in TUFLOW is based on LiDAR survey which has been sampled on a 3 m (min) grid and does not necessarily incorporate localised features which can influence flooding behaviour in individual allotments.

Flood depths are therefore approximate only and require interpretation by a suitably qualified engineer to determine flooding behaviour in individual allotments. Any assessment of flooding in individual allotments may also require a site survey.

The allotment boundaries shown are based on the NSW State Database obtained from the Six Maps online database and may not represent the true property boundaries in the study area


LEGEND

- LGA Boundary
- Two-Dimensional Model Boundary
- Modelled Stormwater Drainage System
- Village Centre
- Homesteads

**BOGAN GATE
FLOOD RISK MANGEMENT STUDY AND PLAN**

Figure B1.3
(Sheet 3 of 3)

INDICATIVE EXTENT AND DEPTHS OF INUNDATION
5% AEP



Indicative Depth of Inundation (m)



400 0 400 800 1,200 m
Scale: 1:40,000

Lyll & Associates

NOTE:

The ground surface model incorporated in TUFLOW is based on LiDAR survey which has been sampled on a 3 m (min) grid and does not necessarily incorporate localised features which can influence flooding behaviour in individual allotments.

Flood depths are therefore approximate only and require interpretation by a suitably qualified engineer to determine flooding behaviour in individual allotments. Any assessment of flooding in individual allotments may also require a site survey.

The allotment boundaries shown are based on the NSW State Database obtained from the Six Maps online database and may not represent the true property boundaries in the study area


LEGEND


- LGA Boundary
- Two-Dimensional Model Boundary
- Modelled Stormwater Drainage System
- Village Centre
- Homesteads


**BOGAN GATE
FLOOD RISK MANGEMENT STUDY AND PLAN**

Figure B1.4
(Sheet 2 of 3)


INDICATIVE EXTENT AND DEPTHS OF INUNDATION
2% AEP







Indicative Depth of Inundation (m)



400 0 400 800 1,200 m
Scale: 1:40,000

Lyall & Associates

NOTE:

The ground surface model incorporated in TUFLOW is based on LiDAR survey which has been sampled on a 3 m (min) grid and does not necessarily incorporate localised features which can influence flooding behaviour in individual allotments.

Flood depths are therefore approximate only and require interpretation by a suitably qualified engineer to determine flooding behaviour in individual allotments. Any assessment of flooding in individual allotments may also require a site survey.

The allotment boundaries shown are based on the NSW State Database obtained from the Six Maps online database and may not represent the true property boundaries in the study area


LEGEND


- LGA Boundary
- Two-Dimensional Model Boundary
- Modelled Stormwater Drainage System
- Village Centre
- Homesteads


BOGAN GATE FLOOD RISK MANGEMENT STUDY AND PLAN

Figure B1.5
(Sheet 2 of 3)

INDICATIVE EXTENT AND DEPTHS OF INUNDATION
0.5% AEP







Indicative Depth of Inundation (m)

- 0.10 to 0.20
- 0.20 to 0.30
- 0.30 to 0.40
- 0.40 to 0.50
- 0.50 to 0.60
- 0.60 to 0.70
- 0.70 to 0.80
- 0.80 to 0.90
- 0.90 to 1.00
- > 1.00



100 0 100 200 300 m
Scale: 1:10,000

Lyall & Associates

NOTE:

The ground surface model incorporated in TUFLOW is based on LiDAR survey which has been sampled on a 3 m (min) grid and does not necessarily incorporate localised features which can influence flooding behaviour in individual allotments.

Flood depths are therefore approximate only and require interpretation by a suitably qualified engineer to determine flooding behaviour in individual allotments. Any assessment of flooding in individual allotments may also require a site survey.

The allotment boundaries shown are based on the NSW State Database obtained from the Six Maps online database and may not represent the true property boundaries in the study area

LEGEND

- LGA Boundary
- Two-Dimensional Model Boundary
- Modelled Stormwater Drainage System
- Village Centre
- Homesteads

BOGAN GATE
FLOOD RISK MANGEMENT STUDY AND PLAN

Figure B1.6
(Sheet 3 of 3)


INDICATIVE EXTENT AND DEPTHS OF INUNDATION
0.2% AEP

APPENDIX C

SUGGESTED WORDING FOR INCLUSION IN PARKES SHIRE DEVELOPMENT CONTROL PLAN

LIST OF FIGURES (APPENDIX C)

- C1.1 Extract of Parkes Shire Flood Planning Map at Bogan Gate
- C1.2 Extract of Parkes Shire Flood Planning Constraint Category Map at Bogan Gate



LEGEND

Main Stream Flooding Flood Planning Area
(Refer Schedule 2A of Appendix C)

Main Stream Flooding Special Flood Considerations
Zone (Refer Schedule 2A of Appendix C)

Major Overland Flow Flood Planning Area
(Refer Schedule 2B of Appendix C)

Major Overland Flow Special Flood Considerations
Zone (Refer Schedule 2B of Appendix C)

N

200 0 200 400 600 m

Scale: 1:20,000

NOTE:

The ground surface model incorporated in TUFLOW is based on LiDAR survey which has been sampled on a 3 m (min) grid and does not necessarily incorporate localised features which can influence flooding behaviour in individual allotments.

Flood depths are therefore approximate only and require interpretation by a suitably qualified engineer to determine flooding behaviour in individual allotments. Any assessment of flooding in individual allotments may also require a site survey.

The allotment boundaries shown are based on the NSW State Database obtained from the Six Maps online database and may not represent the true property boundaries in the study area

LEGEND

Two-Dimensional Model Boundary

●

Modelled Stormwater Drainage System

Village Centre

●

Homesteads


BOGAN GATE

FLOOD RISK MANGEMENT STUDY AND PLAN

Figure C1.1

EXTRACT OF PARKES SHIRE FLOOD PLANNING MAP AT BOGAN GATE

Lyall & Associates



NOTE:
The ground surface model incorporated in TUFLOW is based on LiDAR survey which has been sampled on a 3 m (min) grid and does not necessarily incorporate localised features which can influence flooding behaviour in individual allotments.

Flood depths are therefore approximate only and require interpretation by a suitably qualified engineer to determine flooding behaviour in individual allotments. Any assessment of flooding in individual allotments may also require a site survey.

The allotment boundaries shown are based on the NSW State Database obtained from the Six Maps online database and may not represent the true property boundaries in the study area.

LEGEND

- Two-Dimensional Model Boundary
- Modelled Stormwater Drainage System
- Village Centre
- Homesteads

BOGAN GATE
FLOOD RISK MANGEMENT STUDY AND PLAN
Figure C1.2

Lyall & Associates

EXTRACT OF PARKES SHIRE FLOOD PLANNING CONSTRAINT CATEGORY MAP AT BOGAN GATE